



WISA®-Pro Facade

Time saving solutions for modern and traditional facades - suitable for use in all exterior cladding applications.

Unfinished, primed and pine oil-treated options available.

The wide choice of dimensions, profiles and qualities ensures all needs of today's house builder are met.

Once installed correctly, WISA-Pro Facade has low maintenance costs, long service life and excellent insulation properties.

Raw material

Slow grown, live-knotted homogenous whitewood, carefully selected from PEFC certified forests and tailor-made for this end use by UPM's own sawmills. The raw material is kiln dried specifically for outdoor end use.

Planing and profiles

WISA-Pro Facade is produced either with a fine sawn visible surface or planed four sides. WISA-Pro Facade is planed inner side up – this means the naturally more weather-resistant heartwood is on the visible surface. All standard profiles, DIN-standard, rebated shiplap, loglap etc. are available, we also offer tailor-made profiles to order. We deliver the product end matched, hence reducing waste at installation.

Dimensions and lengths

Fine sawn visible surface

Nominal fine sawn	Actual fine sawn	Normal lengths, LP
19 x 100	18 x 95	3.6 - 5.4 m
19 x 125	18 x 120	3.6 - 5.4 m
19 x 150	18 x 145	3.6 - 5.4 m
23 x 100	21 x 95	3.6 - 5.4 m
23 x 125	21 x 120	3.6 - 5.4 m
25 x 100	23 x 95	3.6 - 5.4 m
25 x 125	23 x 120	3.6 - 5.4 m
25 x 150	23 x 145	3.6 - 5.4 m
32 x 125	28 x 120	3.6 - 5.4 m
32 x 150	28 x 145	3.6 - 5.4 m
32 x 175	28 x 170	3.6 - 5.4 m
32 x 195	28 x 195	3.6 - 5.4 m

Planed four sides

Nominal planed four sides	Actual planed four sides	Normal lengths, LP
22 x 100	18 x 95	3.6 - 5.4 m
22 x 125	18 x 120	3.6 - 5.4 m
22 x 150	18 x 145	3.6 - 5.4 m
25 x 100	21 x 95	3.6 - 5.4 m
25 x 125	21 x 120	3.6 - 5.4 m
32 x 125	28 x 120	3.6 - 5.4 m
32 x 150	28 x 145	3.6 - 5.4 m
32 x 175	28 x 170	3.6 - 5.4 m
32 x 195	28 x 195	3.6 - 5.4 m

Standard lengths in 30 cm modules are 3.6 – 5.4 m, most common lengths being 3.9/4.2/4.5/4.8 m. WISA-Pro Facade can also be delivered in finger jointed precise lengths up to 6.0 m.

WISA®-Pro Facade

Surface treatment options

Priming

Primed WISA-Pro Facade are manufactured using water-soluble, environmentally friendly alkyd paint (see primer colour range on the left). On request, WISA-Pro Facade can also be delivered finished with top coat.

WISA-Pro Facade is supplied in 9 standard colours, customers' own colours can be produced to order.


Pine oil treatment

WISA-Pro Facade⁺ is a special outdoor cladding product, treated with an environmentally friendly pine oil. This 2-step treatment used at our mill gives better protection to the wood and improves the covering capacity of the primer. During the first step, each piece is treated with an oil based anti-mildew agent that penetrates into the piece. The second step involves pre-painting of the piece using a water-soluble alkyd paint. Painting conditions are carefully controlled and all operations at the mill are strictly regulated by an in-house quality control system.

Packaging

WISA-Pro Facade products are delivered in bundles of 4 pieces, each carefully packed and protected on five sides. Customer-specific packaging is available on request.

Samples are available in standard profiles to show the priming and finish quality.




F157



X002




9203



X150



X153



Y053



55 Queen Street
Maidenhead, Berks, SL6 1LT

Tel. 01628 513300
Fax 01628 513400

woodltd@upm-kymmene.com
www.wisa.com

